

HOPING FOR A LARGE FISH SAMPLE

# APPENDIX A EFFLUENT ON-SITE AND OFF-SITE MONITORING PROGRAM

#### 1989 EFFLUENT ON-SITE AND OFF-SITE MONITORING PROGRAM

The following schedule represents the West Valley Demonstration Project's routine environmental monitoring program which was in place in 1989. This schedule meets or exceeds the minimum program needed to satisfy the requirements of the Department of Energy (DOE) Order 5400.1, which superseded DOE 5484.1A, Chapter III, in late 1988. It also meets requirements of further DOE 5400 orders currently being drafted. Specific methods and recommended monitoring program elements are found in DOE/EP-0096, "Effluent Monitoring," and DOE/EP-0023, "Environmental Surveillance," which are the bases for selecting most of the schedule specifics. Additional monitoring is mandated by Operational Safety Requirements (OSRs) and air and water discharge permits (40 CFR 61 and SPDES), which also require a formal report. These specific cases are identified in the schedule under MONITORING/REPORTING REQUIREMENTS. The overall environmental program schedule is referenced in OSR/TR-GP-4.

#### Summary of Monitoring Program Changes Implemented in 1989

Significant 1989 program changes were limited to collecting samples from new sample points and to changes in frequency of sampling and analyses, in response to changes in regulations coming into effect in late 1988 and in 1989.

#### **Schedule of Environmental Sampling**

The following table is a schedule of environmental sampling at the West Valley Demonstration Project. Locations of the sampling points are shown in Figures A-1 through A-9. The index below is a list of the codes for the various sample locations. Table headings in the schedule are as follows:

- Sample Location and ID code. The physical location from which the sample is collected is described. The ID is a seven-character code: The first character identifies the sample medium as Air, Water, Soil/Sediment, Biological, or Direct Measurement. The second character specifies oN-site or oFf-site location. The remaining characters describe the specific location (e.g., AFGRVAL is Air, oFf-site, at GReat VALley).
- Monitoring/Reporting Requirements. The basis for monitoring that location and any additional references to permits or OSRs are noted, as well as the reports generated from the sample data.
- Sampling Type/Medium. This describes the collection method and the physical characteristics of the medium.
- Collection Frequency. Indicates how often the samples are collected or retrieved.
- Total Annual Samples. The number of discrete physical samples collected annually, not including composites of collected samples, is noted.
- Analysis Performed/Composite Frequency. The individual analyses of the samples or composites of samples and the frequency of analyses is described.

# **Index of Environmental Monitoring Program Sample Points**

## On-Site Effluent: Air (Figure A-1)

ANSTACK - Main Plant	A-6
ANSTSTK - Supernatant Treatment	A-6
ANCSSTK - Cement Solidification	A-7
ANCSRFK - Size Reduction Facility	A-7
ANSUPCV - Supercompactor	A-8
On-Site Liquid Effluent and Surface Water (Figure A-2)	
WNSP001 - Lagoon 3 Weir Point	A-9
WNSP006 - Facility Main Drainage	A-10
WNSP007 - Sanitary and Utility Waste Discharge	A-10
WNSWAMP - Swamp Drainage Point	A-11
WNSW74A - Swamp Drainage Point	A-11
WNSP008 - French Drain LLWT Area	A-11
WNSP005 - South Facility Drainage	A-12
WNCOOLW - Cooling Tower*	A-12
WNDRNKW - Potable Water*	A-12
WNSP003 - SDA Lagoon (NYSERDA)*	A-12
WNFRC67 - Frank's Creek East	A-13
WNERB53 - Erdman Brook	A-13
WNNDADR - Disposal Area Drainage	A-13
WNDCELD - Drum Cell Drainage	A-13
WNSTAW Series - Standing Water*	A-14
On-Site Groundwater and Seeps (Figure A-3)	
HLW Tank Unit Wells and WNDMPNE	A-15
Lagoon Unit Wells, WNGSEEP and WNSP008	A-15
NDA Unit Wells	A-15
Facility Area Wells	A-16
NDA Area Wells	A-16
Fuel Storage Tank Well	A-16
Off-Site Surface Water (Figure A-4)	
WFFELBR - Cattaraugus at Felton Bridge	A-17
WFBCTCB - Buttermilk Creek at Thomas Corners	A-17
WFBCBKG - Buttermilk Creek Background	A-17
Off-Site Groundwater (Figures A-5 and A-9)	
WFWEL Series - Private local wells	A-18

<sup>\*</sup> Not detailed on map

# **Index of Environmental Monitoring Program Sample Points**

### Off-Site Ambient Air (Figure A-6)

AFFXVRD - Fox Valley Sampler	A-19
AFTCORD - Thomas Corners Sampler	A-19
AFRT240 - Route 240 Sampler	A-19
AFRSPRD - Rock Springs Road Sampler	A-19
AFGRVAL - Great Valley (Background)	A-19
AFSPRVL - Springville Sampler	A-19
AFWEVAL - West Valley Sampler	A-19
AFDNKRK - Dunkirk (Background)	A-19
AFBOEHN - Dutch Hill Road Sampler	A-19
AFDHFOP - Dutch Hill Fallout*	A-20
AFFXFOP - Fox Valley Fallout*	A-20
AFTCFOP - Thomas Corners Fallout	A-20
AF24FOP - Route 240 Fallout	A-20
Off-Site Soil/Sediment*	
SFSOL Series - Air Sampler Area Soil	A-20
SFTCSED - Thomas Corners Road Sediment	A-20
SFBCSED - Buttermilk Creek Background Sediment	A-20
SFSDSED - Cattaraugus Creek at Springville Dam	A-20
SFBISED - Cattaraugus Creek Background Sediment	A-20
SFCCSED - Cattaraugus Creek at Felton Bridge	A-20
Off-Site Biological (Figures A-5 and A-9)	
BFFCATC - Cattaraugus Creek, Fish, Downstream	A-21
BFFCATD - Cattaraugus Creek, Fish, Downstream below Dam	A-21
BFFCTRL - Cattaraugus Creek, Fish, Background	A-21
BFMREED - NNW Milk	A-21
BFMCOBO - WNW Milk	A-21
BFMWIDR - SE Milk	A-21
BFMHAUR - SSW Milk	A-21
BFMCTLS - Milk, South, Background	A-21
BFMCTLN - Milk, North, Background	A-21
BFVNEAR - Produce, Near-site	A-22
BFVCTRL - Produce, Background	A-22
BFHNEAR - Forage, Near-site	A-22
BFHCTLS - Forage, South, Background	A-22
BFHCTLN - Forage, North, Background	A-22
BFBNEAR - Beef, Near-site	A-22
BFBCTRL - Beef, Background	A-22
BFDNEAR - Venison, Near-site	A-22
BFDCTRL - Venison, Background	A-22
Direct Measurement Dosimetry: Thermoluminescent LiF Dosimeters (I	Figures A-7, A-8, and A-9)
DFTLD Series - Off-Site Dosimetry	A-23
DNTLD Series - On-Site Dosimetry	A-24
* Not detailed on map	

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Main Plant Ventilation Exhaust Stack ANSTACK	Airborne radioactive effluent point including LWTS and Vitrification Off-	Continuous off- line air particulate monitor	Continuous measurement of fixed filter, replaced weekly	N/A	Real time alpha and beta monitoring
Supernatant Treatment System (STS) Ventilation Exhaust ANSTSTK	Required by: OSR/TR-GP-1 40 CFR 61	Continuous off- line air particulate filter	Weekly	104 (52 per location)	Gross alpha/beta, gamma isotopic.* Quarterly composite for Sr-90, Pu/l isotopic, Am-241, gamma isotopic
	Reported: Monthly Environmental Monitoring Trend Analysis	Continuous off- line desiccant column for water vapor collection	Weekly	104 (52 per location)	н-3
	Annual Effluent and On-Site Discharge Report	Continuous off- line charcoal cartridge	Weekly	104 (52 composited to 4 per location)	Quarterly composite for I-129
	Annual Environmental Monitoring Report				
	Air Emission Annual Report (NESHAP)	•			

Weekly gamma isotopic only if gross activity rises significantly

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Cement Solidification System (CSS) Ventilation Exhaust ANCSSTK	Airborne radioactive effluent point  Required by: OSR/TR-GP-1 40 CFR 61	Continuous off- line air particulate monitor	Continuous measurement of fixed filter, replaced weekly	N/A	Real time alpha and beta monitoring
Contact Size Reduction Facility Exhaust ANCSRFK	Reported: Monthly Environmental Monitoring Trend Analysis	Continuous off- line air particulate filter	Weekly	104 (52 per location)	Gross alpha/beta, gamma isotopic.* Quarterly composite for Sr-90, Pu/U isotopic, Am-241, gamma isotopic.
	Annual Effluent and On-site Discharge report	Continuous off- line charcoal cartridge.	Weekly	104 (52 composited to 4 per location)	Quarterly composite for I-129
	Annual Environmental Monitoring Report				-
	Air Emissions Annual Report (NESHAP)		-		

<sup>\*</sup>Weekly gamma isotopic only if gross activity rises significantly.

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Supercompactor Exhaust	Airborne radioactive effluent point	Continuous off- line air	Continuous measurement of	N/A	Real time beta monitoring
ANSUPCV	Required by: OSR/TR-GP-1 40 CFR 61	particulate monitor during operation (maximum of 26	fixed filter, collected and replaced every seven operating	26	Filters for gross alpha/beta, gamma isotopic* upon collection
	Reported:	operating weeks expected)	days, or at least monthly when unit is	26 composited to 4	Quarterly composites: filters for Sr-90, Pu/U isotopic, Am-241, gamma
	Environmental Monitoring Trend Analysis		operated		isotopic
	Annual Effluent and On-site Discharge Report				
	Annual Environmental - Monitoring Report				
	Air Emissions Annual Report (NESHAP)				-

Weekly gamma isotopic only if gross activity rises significantly.

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Lagoon 3 Discharge Weir WMSP001	Primary point of liquid effluent batch release Required by: OSR/TR-GP-2 SPDES Permit Reported: Monthly NPDES DMR	Grab liquid	Daily, during Lagoon 3 discharge	40-80	Daily: gross beta, conductivity, pH. Every sixth daily sample: gross alpha/beta, H-3, Sr-90, gamma isotopic. Weighted monthly composite of daily samples: gross alpha/beta, H-3, C-14, Sr-90, I-129, gamma isotopic, Pu/U isotopic, Am-241
	Annual Effluent and On-site Discharge Report	Composite liquid	Twice during discharge, near start, and near end	8-10	Two 24 hour composites for Al, NH <sub>3</sub> , As, BOD-5, Fe, Zn, pH, suspended solids; SO <sub>2</sub> , NO <sub>2</sub> , NO <sub>2</sub> , Cr <sup>+O</sup> , Cd, Cu, PD
	Annual Environmental Monitoring Report	Grab liquid	Twice during discharge, same as composite	8-10	Settleable solids, pH, cyanide, oil and grease
		Composite liquid	Annually	1	Annually, a 24 hour composite for: Cr, Ni, Se, Ba, Sb
		Grab liquid	Annually	1	Chloroform

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Erdman Brook at Security Fence UNESPOO6	Combined facility liquid discharge  Required by: OSR/TR-GP-2  Reported: Monthly Environmental Monitoring Trend Analysis  Annual Environmental Monitoring Report	Continuous proportional sample liquid	<b>*Wee</b> k≬y	52	Gross alpha/beta, H-3, pH, conductivity. Monthly composite: gamma isotopic and Sr-90. Quarterly composite: C-14, I-129, Pu/U isotopic, Am-241.
Sanitary Waste Discharge WMSP007	Liquid effluent point for sanitary and utility plant combined discharge	24 hour composite liquid	3/month	36	Gross alpha/beta, H-3, suspended solids, NH <sub>3</sub> , BOO-5, Fe
	Required by: SPDES Permit	Grab liquid	Weekly	52	pH, settleable solids
	Reported: Monthly NPDES DMR	Grab liquid	Annually	1	Chloroform
	Monthly Environmental Monitoring Trend Analysis	In-line monitor with alarm	Continuous	N/A	pH .
	Annual Effluent and On-site Discharge Report				
	Annual Environmental Monitoring Report				

<sup>\*</sup>Samples were collected simultaneously for NYSDOH.

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
N.E. Swamp Drainage UNSUAMP*	Site surface drainage	Grab liquid	Monthly	24 (12 per location)	Gross alpha/beta, H-3, pH
North Swamp Drainage <b>UNSU74A</b>	Reported: Annual Effluent and On-site Discharge Report				
French Drain WNSP008	Drains subsurface water from LLWT Lagoon area	Grab liquid	3/month	36	pH, conductivity, BOD-5, Fe
	Required by: SPDES Permit		Monthly	12	Gross alpha/beta, H-3
	Reported: Monthly NPDES DMR		Annually	1	Ag,Zn
	Annual Effluent and On-Site Discharge Report				
	Annual Environmental Monitoring Report				

<sup>\*</sup>Samples collected simultaneously for NYSDOH.

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING . REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Condensate and Cooling Water Ditch UMSP005	Combined drainage from facility yard area	Grab liquid	Monthly	12	Gross alpha/beta, H-3, pH
	Reported: Internal Review				· ·
Cooling Tower Basin WMCCOOLW	Cools plant utility steam system water  Reported: Internal Review	Grab liquid	Monthly	12	Gross alpha/beta, M-3, pH
Site Potable Water <b>UNDRNKU</b>	Source of water within site perimeter	Grab liquid	Monthly	12	Gross alpha/beta, H-3, pH, conductivity
	Reported: Internal Review		Annually	2	Toxic metals, pesticides chemical pollutants
SDA Holding	State Disposal Area	Grab liquid	Annually (as	1	Gross alpha/beta, H-3,
Lagoon UNSP003	Holding Lagoon	ar dar virquire	required)		C-14, pH, gamma isotopic, Sr-90, I-129, Pu/U isotopic

Reported: Annual Environmental Monitoring Report NYSERDA

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Frank's Creek E of SDA WNFRC67	Drains NYS Low-Level Waste Disposal Area	Grab liquid	*Monthly	12	Gross alpha/beta, H-3, pH
	Reported: Internal review NYSERDA				·
Erdman Brook N of Disposal Areas WNERB53	Drains NYS and WVDP disposal areas	Grab liquid	Weekly	52	Gross alpha/beta, H-3, рН
	Reported: Internal review NYSERDA		*Monthly		
Ditch N of WVDP NDA & SDA WNNDADR	Drains WVDP disposal and storage area	Composite continuous liquid	Weekly	52	pH Monthly composite: gross alpha/beta, gamma isotopic, H-3. Quarterly composite: Sr-90, I-129
	Reported: Internal review				
	Environmental Monitoring Trend Analysis				
Drainage S of Drum Cell WNDCELD	Reported: Internal review	Grab líquid	Weekly	52	pH Monthly composite: gross alpha/beta, gamma isotopic, H-3. Quarterly composite: Sr-90, I-129

<sup>\*</sup>Samples were collected simultaneously for NYSDOH.

ANALYSES PERFORMED/

COMPOSITE FREQUENCY

Gross alpha/beta, H-3, pH, conductivity, chloride, Fe, Mn, Na, phenols, sulfate

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS**	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES
On-site Standing Water (ponds not receiving effluent)	Water within vicinity of plant airborne or ground water effluent	Grab liquid	Annually	7-10*
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	<u>Reported:</u> Internal Review			
Test Pit N of HLW Area WNSTAW1				
Slough SW of RTS Drum Cell WNSTAW2				
Pond SE of Heinz Road WNSTAWS				
Border Pond S of AFRT240 UNSTAU6				
Border Pond SW of DFTLD13 WNSTAW5				
Borrow Pit NE of Project Facilities UNSTAU6				
Pond SW of Project Facilities W of				
Rock Springs Road WNSTAW7				
Slough N of Quarry Creek UNSTAW8				
North Reservoir Near Intake				
Background Pond at Sprague Brook				

Number of points sampled will depend upon on-site ponding conditions during the year.

Maintenance Building UNSTAUB

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
On-site Ground- water	Groundwater monitoring wells around site solid waste management units	Grab liquid	4 times semiannually (8 samples yearly per well)**	144	Gross alpha/beta, H-3, gamma isotopic, chloride, sulfate, phenols, F, nitrate, TOC, TOH, As, Ba, Cs, Cr, Fe, Pb, Mn, Hg, Se, Ag, Na
HLW Tank GW Monitoring Unit - Wells: LINLW 80-2 86-7 86-8 86-9 86-12* Surface: LAGOON GW Monitoring Unit - Wells: LINLW 86-6 86-3 86-4 86-5 80-5 80-5 80-5 Surface: LINGSEEP LINGSEEP LINGSEEP LINGSPOOS NDA GW Monitoring Unit - Wells: LINLW 83-1D 86-10	Reported: Annual Environmental Monitoring Report	Direct measurement of sample discharge water	Before and after grab sample collection	288 (2 measurements per sample collection event)	Temperature, pH, conductivity
86-11 82-10					

<sup>\*</sup>Serves former Cold Dump

<sup>\*\*</sup>Sampling and analysis conducted as outlined in the RCRA Groundwater Technical Enforcement Guidance Document (EPA OSWER 9950.1) at the Statistical Analysis of Monitoring Data at RCRA Facilities (EPA/530-SW-89-026).

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
On-site Ground- water	Groundwater monitoring wells around site facilities	Grab liquid	Semiannually	22* (2 per location)	Gross alpha/beta, H-3, gamma isotopic
Facility/Plant Area Wells: WMW 80-3 80-4	<u>Reported</u> : Annual Environmental Monitoring Report	Direct measurement of sample discharge water	Before and after grab sample collection	44* (two measurements per sample collection event)	Temperature, pH, conductivity
NDA Area Wells: WNW 82-1A 82-1B 82-1C 82-2B 82-2C 82-3A 82-4A1 82-4A2					
Fuel Storage Tank Subsurface Monitoring Well: WMW 86-13	Reported: Annual Environmental Monitoring Report	Grab liquid	Semiannually	2	Gross alpha/beta, H-3, gamma isotopic, phenols, TOC, benzene, toluene, xylene
		Direct measurement of discharge water	Before and after grab sample collection	4	Temperature, pH, conductivity

<sup>\*</sup>Number of samples variable; occasionally wells are dry.

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Cattaraugus Creek at Felton Bridge <b>UFFELBR</b>	Unrestricted surface waters receiving plant effluents	Flow weighted continuous liquid	Weekly *Weekly for monthly composite	52	Gross alpha/beta, H-3, pH. Monthly composite for gamma isotopic and Sr-90
	Reported: Monthly Environmental Monitoring Trend Analysis Annual Environmental				
	Monitoring Report				
Buttermilk Creek, Upstream of Cattaraugus Creek Confluence at Thomas Corners Road WFBCTCB	Restricted surface waters receiving plant effluents  Reported: Annual Environmental Monitoring Report	Composite continuous liquid	*Biweekly	26	Monthly for gross alpha/beta, H-3, pH. Quarterly composite for gamma isotopic and Sr-90
Buttermilk Creek near Fox Valley <b>WFBCBKG</b>	Restricted surface water background  Reported: Monthly Environmental Monitoring Trend Analysis	Composite continuous liquid	*Biweekly	26	Monthly for gross alpha/beta, H-3. Quarterly composite for gamma isotopic and Sr-90
	Annual Environmental Monitoring Report				

<sup>\*</sup>Samples are split with NYSDOH.

ANALYSES PERFORMED/ COMPOSITE FREQUENCY

Gross alpha/beta, H-3, gamma isotopic, pH,

conductivity

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES
Wells near WVDP outside WNYNSC Perimeter	Drinking supply groundwater near facility	Grab liquid	Biennially (Background Well sampled annually)	6 (5 + background
3.0 km WNW WFWEL01	<u>Reported</u> : Annual Environmental Monitoring Report		are watty)	well each year of collection)*
1.5 km NV VFVELO2				
4.0 km NW WFWELO3				
3.0 km NW WFWELO4				
2.5 km SW WFWEL05				
29 km S <b>WFWELO6</b> (background)				
4.0 km NNE WFWELO7				
2.5 km ENE VFWELO8				
3.0 km SE <b>WFWEL09</b>				

7.0 km N

<sup>&</sup>quot;In 1989 all 10 wells were sampled.

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
3.0 km SSE at Fox Valley AFFXVRD	Particulate air samples around WNYNSC perimeter	Continuous air particulate filter	Weekly	468 (52 per location)	Gross alpha/beta
3.7 km NNW at Thomas Corners Road AFTCORD	<u>Reported</u> : Annual Environmental Report				Quarterly composite for Sr-90, gamma isotopic
2.0 km NE on Route 240 AFRT240+	Monthly Environmental Monitoring Trend Analysis (four sites only+)	Continuous desiccant column for water vapor collection	Weekly (2 sites only**)	104 (52 per site)	н-3
1.5 km NW on Rock Springs Road AFRSPRD***		Continuous charcoal cartridge	Weekly (2 sites only**)	104 (52 per site)	Quarterly composite for I-129
29 km S at Great Valley (background) AFGRVAL**+					
7 ion 11 an					

7 km N at Springville AFSPRVL

6 km SSE at West Valley AFWEVAL

50 km W at Dunkirk (background) AFDNKRK

2.3 km SW on Dutch Hill Road AFBOEHN+

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
2.5 km SW AFDHFOP 3.0 km SSE AFFXFOP	Collection of fallout particulate and precipitation around WNYNSC perimeter	Integrating liquid	Monthly	48 (12 per site)	Gross alpha/beta, H-3, pH
3.7 km NNW AFTCFOP	<u>Reported:</u> Annual Environmental Report				
2.0 km NE AF24FOP					
Surface Soil (at each of nine air samplers plus 26 km SSW at Little Valley) SFSOL - Series	Long-term fallout accumulation  Reported: Annual Environmental Monitoring Report (year of collection)	Surface plug composite soil	Annually	10	Gamma isotopic, Sr-90, Pu-239, Am-241
Buttermilk Creek at Thomas Corners Road SFTCSED**	Deposition in sediment downstream of facility effluents	Grab stream sediment	Semiannually 1st sample of SFBCSED and SFSDSED each spring*	10	Gross alpha/beta, isotopic gamma and Sr-90
Buttermilk Creek at Fox Valley Road (background) SFBCSED**	<u>Reported:</u> Annual Environmental Monitoring Report		Annually (2 sites only**)	2	U/Pu isotopic, Am-241
Cattaraugus Creek at Springville Dam SFSDSED					
Cattaraugus Creek at Bigelow Bridge (background) SFBISED					
Cattaraugus Creek at Felton Bridge SFCCSED					

<sup>\*</sup>Sample to be split with NYSDOH.

<sup>\*\*</sup>Analysis on one of two semiannual collections.

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Cattaraugus Creek downstream of the Buttermilk Creek Confluence BFFCATC	Fish in waters downstream of facility effluents  Reported: Annual Environmental Monitoring Report	Individual collection, biological	Semiannually  *BFFCATC and BFFCTRL shared with NYSDOH, BFFCATD as sample is available	6 (each sample is 10 fish)	Isotopic gamma and Sr-90 in edible portions of each individual fish
Cattaraugus Creek downstream of Springville Dam BFFCATD  Control Sample from nearby stream not affected by WVDP (7 km or more upstream of site effluent point) BFFCTRL					
Dairy Farm, 3.8 km NNW BFMREED Dairy Farm, 1.9 km WNW BFMCOBO	Milk from animals foraging around facility perimeter  Reported: Annual Environmental Monitoring Report	Grab biological	Monthly (*BFMREED, BFMCOBO, BFMCTLS, BFMCTLN)	48 (12 per site)	Gamma isotopic, Sr-90, H-3 and I-129 on annual samples and quarterly composites of monthly samples
Dairy Farm, 3.5 km SE of site BFMWIDR			Annual (BFMWIDR, BFMHAUR)	2	
Dairy Farm 2.5 km SSW BFMHAUR					
Control location 25 km S BFMCTLS					
Control location 30 km N BFMCTLN					· .

<sup>\*</sup>Samples shared with NYSDOH

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
(3) Nearby locations BFVNEAR	Fruit and vegetables grown near facility perimeter downwind if possible	Grab biological	*Annually, at harv <del>e</del> st	6	Gamma isotopic and Sr-90 analysis of edible portions, H-3 in free moisture
(3) Remote locations (16 km or more from facility) BFVCTRL	Reported: Annual Environmental Monitoring Report				i .
Beef cattle forage from near site location N BFHNEAR		Grab biological	Annually	2	Gamma isotopic, Sr-90
Milk cow forage from control south location or north location BFHCTLS or BFHCTLN					-
Beef animal from nearby farm in downwind direction BFBMEAR	Meat-beef foraging near facility perimeter, downwind if possible	Grab biological	Semiannually  *2nd sample (each fall) to NYSDOH	4	Gamma isotopic and Sr-90 analysis of meat
Beef animal from control location (16 km or more from facility) BFBCTRL	<u>Reported</u> : Annual Environmental Monitoring Report				
In vicinity of the site (3) BFDMEAR	Meat-deer foraging near facility perimeter	Individual collection biological	*Annually, during hunting season	3	Gamma isotopic and Sr-90 analysis of meat
Control animals (3) (16 km or more from facility) BFDCTRL	<u>Reported</u> : Annual Environmental Monitoring Report		*During year as available	3	

<sup>\*</sup>Sample to be split with NYSDOH


SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Thermolumines- cent Dosimetry (TLD) off-site: DFTLD Series	Direct radiation around facility	Integrating Lif TLD	Quarterly	460 (5 TLD's at each of 23 locations, collected 4 times per year)	Quarterly gamma radiation exposure
(16) at each of 16 compass sectors, at nearest accessible perimeter point #1-16	Reported: Monthly Environmental Monitoring Trend Analysis Annual Environmental Monitoring Report				·
"5 Points" land-fill, 19 km SW (background) #17					
1500 m NW (downwind receptor ) #20					
Springville 7 km N #21					
West Valley 5 km SSE #22					
Great Valley, 29 km S (background) #23					
Dunkirk, 50 km NW (background) #37					
Sardinia-Savage Rd. 24 km NE					

(background) #41

SAMPLE LOCATION AND I.D. CODE	MONITORING/REPORTING REQUIREMENTS	SAMPLING TYPE/MEDIUM	COLLECTION FREQUENCY	TOTAL ANNUAL SAMPLES	ANALYSES PERFORMED/ COMPOSITE FREQUENCY
Thermolumines- cent Dosimetry (TLD) on-site: DNTLD Series	Direct radiation on facility grounds	Integrating Lif	Quarterly	360 (5 TLD's at each of 18 sites collected 4 times per year)	Quarterly gamma radiation exposure
(3) at corners of SDA #18, 19, 33	Reported: Monthly Environmental Monitoring Trend Analysis				
(9) at security fence around site #24, 26-34	Annual Environmental Monitoring Report				
(5) On-site near operational areas #35, 36, 38-40					-
Rock Springs Road 500 m NNW of plant #25					

Figure A-1. Location of On-Site Air Effluent Points.

Figure A-2. Sampling Locations for On—Site Surface Water.






Figure A-3. Location of On—Site Groundwater Monitoring Points.




Figure A-4. Location of Off—Site Surface Water Samplers.




Figure A-5. Near-Site Drinking Water and Biological Sample Points - 1989.




Figure A-6. Location of Perimeter Air Samplers.




Figure A-7. Location of Off—Site Thermoluminescent Dosimetry (TLD).




FIGURE A-9. ENVIRONMENTAL SAMPLE POINTS MORE THAN 5 KM FROM THE WVDP SITE